



## Model M



FM Approved

175 PSI Rated

6" Meter Dial

270° Arc on Dial

Meter is liquid-filled, bellows type

Accurate to within  $\pm 0.5\%$

Nipple (or T-Bracket, for  $>4"$ )  
welded to venturi to attach meter\*

Venturi available in Butt-Weld (VW-B),  
Grooved (GE), 150# Flanged (VW-F 150#)  
or 300# Flanged (VW-F 300#)

Hoses, fittings, meter & venturi  
are color-coded for easy assembly

Metal installation & operation tag  
is chained to each

## Model K



FM Approved

500 PSI Rated for Butt-Weld (VW-B),  
Grooved (GE), or 300# Flanged (VW-F 300#)  
275 PSI Rated for 150# Flanged (VW-F 150#)

4 $\frac{1}{2}$ " Standard Meter Dial,  
6" Dial Available

90° Arc on Dial

Meter is dry, diaphragm type

Accurate to within  $\pm 2.0\%$

Bracket is welded to venturi  
to attach meter\*

Venturi available in Butt-Weld (VW-B),  
Grooved (GE), 150# Flanged (VW-F 150#)  
or 300# Flanged (VW-F 300#)

Hoses, fittings, meter & venturi  
are color-coded for easy assembly

Metal installation & operation tag  
is chained to each

Adaptable for seawater use in Stainless Steel

